Technical-Data-Sheet

SILICON

Insulating and lubricating oil spray

water repellent prevents from flashover



Product description

Article name	SILICON Spray
Material number	124032
Characteristics	Does not damage rubber, plastics, textiles or varnished surfaces
	Does not damage construction materials
	Does not dry out
	Non-adherent
	Suitable for use as moisture buffer
	Water-resistant
Applications	Elimination or prevention of current leakage, corona discharges, soft short circuits
	Wire feed lubricant
	Insulating
	Protection of high-voltage equipment and tube sockets against flying sparks
	Short-circuit protection
	Can be used as a separating agent for plastics
	Prevents treated components from sticking together

Technical data

Content	0.4 l
Colours	transparent color
Viscosity (20 °C)	1000 cP
Flash point	-97 °C
Density	0.55 g/cm³
Heat resistance min	-50 °C
Heat resistance max	200 °C
Dielectric strength	12 kV/mm

Logistics data

Delivery scope	Insulating and lubricating oil spray
Country of origin	France
Customs tariff number	34039900

EAN-UPC	4010311057262			
Base quantity	1	1	12	900
Base unit of measure	Piece	Piece	Piece	Piece
Alternate quantity	1	1	1	1
Alternative unit of measure	Piece	Tin	Carton	Pal. EU
Lenght	67	67	270	1200
Width	67	67	202	800
Height	200	200	203	1400
Dimension unit	Millimetres	Millimetres	Millimetres	Millimetres
Volume	0.898	0.898	11.072	1344
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	Cubic decimetres
Gross weight	0.355	0.355	4.56	348.5
Net weight	0.355	0.355	4.26	319.5
Weight unit	Kilogram	Kilogram	Kilogram	Kilogram