Technical-Data-Sheet

PLASTIC

Clear varnish

for insulation and sealing



Product description

Article name	PLASTIC Spray
Material number	124049
Characteristics	Can be soldered through
	Does not drip
	Highly resistant
Applications	Sealing
	Elimination or prevention of current leakage, corona discharges, soft short circuits
	Insulation of panel boards, components, wires and cables
	Protective film against pollutants such as acid, alkali, alcohol and moisture
	Sealing of board, wood, leather

Technical data

Content	0.4 l
Colours	transparent color
Drying time	20 minutes
Flash point	-97 °C
Density	0.78 g/cm³
Heat resistance min	-70 °C
Heat resistance max	120 °C
Dielectric strength	21 kV/mm

Logistics data

Delivery scope	Clear varnish
Country of origin	France
Customs tariff number	32082010

EAN-UPC	4010311057286			
Base quantity	1	1	12	900
Base unit of measure	Piece	Piece	Piece	Piece
Alternate quantity	1	1	1	1
Alternative unit of measure	Piece	Tin	Carton	Pal. EU
Lenght	65	65	270	1200
Width	65	65	202	800
Height	200	200	203	1400
Dimension unit	Millimetres	Millimetres	Millimetres	Millimetres
Volume	0.845	0.845	11.072	1344
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	Cubic decimetres
Gross weight	0.389	0.389	4.968	379.1
Net weight	0.389	0.389	4.668	350.1
Weight unit	Kilogram	Kilogram	Kilogram	Kilogram