Technical-Data-Sheet

MR 0

Cast resin straight-through joint

for small cross sections and control cables and signal cables




Universally suitable for connecting polymeric cables or conductors insulated with PVC, PE, XLPE and EPR (e.g. N(A)YY, NYM, TT). Suitable for compression connectors on copper and aluminium conductors. REACH Regulation on the restriction of diisocyanates (for EU countries only). The European Commission amended Annex XVII of the REACH Regulation (EC) (new number 74) with Regulation (EU) 2020/1149, which entered into force on 24 August 2020. In accordance with the new REACH Regulation, appropriate training will be required prior to the industrial or professional use of diisocyanates, adhesives and sealants as of 24 August 2023. All information regarding training materials and training courses is available on the ISOPA/ALIPA website https://www.safeusediisocyanates.eu/

Product description

Article name	MR 05
Material number	124508
Characteristics	Compact dimensions
	Splice area visible before casting
	High-quality transparent shockproof plastic shell
	Funnel clips for easy casting
	Stabilized against UV rays
	Resistant to chemical agents
	Resistant to alkaline earth elements
	Suitable for vertical casting
	Longitudinally and transversely watertight
	High electrical insulating values
	High mechanical strength
	Ready for immediate operation
	Quick, safe and easy assembly
Applications	Indoor
	Outdoor
	Underground
	Water
	Submersible pumps
	Installation ducts
Optional accessory	Funnel set/Filling in funnel (on request)
	Heat shrinkable crimp connectors (see Connecting technology)
	Cleaner UNIVERSAL CLEANER 121 (see Accessories)

Technical data



Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
Length L	180 mm
Heigth H	40 mm
Diameter D	26 mm
Nominal cross section Polymeric cable unarmoured per conductor 1x min	25 mm²
Nominal cross section Polymeric cable unarmoured per conductor 1x max	25 mm²
Nominal cross section Polymeric cable unarmoured per conductor 2x min	6 mm²
Nominal cross section Polymeric cable unarmoured per conductor 2x max	6 mm²
Nominal cross section Polymeric cable unarmoured per conductor 3x min	4 mm²
Nominal cross section Polymeric cable unarmoured per conductor 3x max	4 mm²
Nominal cross section Polymeric cable unarmoured per conductor 4x min	4 mm²
Nominal cross section Polymeric cable unarmoured per conductor 4x max	4 mm²
Nominal cross section Polymeric cable unarmoured per conductor 5x min	2.5 mm²
Nominal cross section Polymeric cable unarmoured per conductor 5x max	2.5 mm²
Diameter cable max	16 mm
Control and signal cable 0,75 mm² Number of conductors	16 Pieces
Control and signal cable 1,5 mm² Number of conductors	8 Pieces

Logistics data

Delivery scope	Cover
	Hydrolysis resistance PUR type EG cast resin
	Packed in practical and easy-to-use two-chamber bags
	Transparent plastic shell
	PVC insulation tape
	Protective gloves
	Funnel clips
	Assembly instructions
Shelf life	40 Month
Country of origin	Germany
Customs tariff number	39095090

EAN-UPC	4010311000015			
Base quantity	1	1	480	
Base unit of measure	Piece	Piece	Piece	
Alternate quantity	1	1	1	
Alternative unit of measure	Piece	Case	Pal. OW	
Lenght	208	208	1200	
Width	159	159	800	
Height	47	47	1130	
Dimension unit	Millimetres	Millimetres	Millimetres	
Volume	1.554	1.554	1084.8	
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	
Gross weight	0.237	0.237	131.96	
Net weight	0.237	0.237	113.76	
Weight unit	Kilogram	Kilogram	Kilogram	