Technical-Data-Sheet

LG

Putty/sealing compound

for sealing of wall ducts



Product description

Article name	LG 250
Material number	125198
Characteristics	Removable
	Halogen-free
	Not harmful to the environment
	Gas-tight and waterproof up to 1.5 bar
	Flexible after hardening
	Superior adhesion to metal, plastics (PVC, XLPE and PE), concrete, artificial and natural stone
	Superior thermodynamic properties
	Superior adhesion to metal, plastics (PVC, XLPE and PE), concrete, artificial and natural stone
	Superior thermodynamic properties
Applications	Outdoor
	Indoor
	Underground
	Water
	Sealing of wall ducts
Family notes	Other sizes available on request.
Optional accessory	Centring aid KZ (see Accessories)
	Cleaner UNIVERSAL CLEANER 121 (see Accessories)

Technical data

Content	250 ml
Flash point of cast resin component (open cup)	200 °C
Flash point of reactant (open cup)	200 °C
Processing time (pot life) 250 ml mixture 20 °C	15 minutes
Processing time (pot life) 250 ml mixture 35 °C	9 minutes
Reaction temperature	60 °C
Hardness	80 Shore A
Density	1.1 g/cm³

Logistics data

Delivery scope	Putty/sealing compound
	Spatula
	Assembly instructions
Shelf life	18 Month
Shelf life description	In aluminium bag
Storage temperatur max	35 °C
Storage temperatur min	15 °C
Country of origin	Germany
Customs tariff number	39095090

EAN-UPC	4010311003832			
Base quantity	1	1	360	
Base unit of measure	Piece	Piece	Piece	
Alternate quantity	1	1	1	
Alternative unit of measure	Piece	Case	Pal. OW	
Lenght	232	232	1200	
Width	185	185	800	
Height	32	32	770	
Dimension unit	Millimetres	Millimetres	Millimetres	
Volume	1.373	1.373	739.2	
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	
Gross weight	0.378	0.378	154.28	
Net weight	0.378	0.378	136.08	
Weight unit	Kilogram	Kilogram	Kilogram	