Technical-Data-Sheet

No. 61

Conductive tape

to control electric fields



Product description

Article name	No. 61
Material number	125590
Characteristics	Printed „CAUTION-CONDUCTING TAPE“ to eliminate danger of confusion
	Self-amalgamating
	Fuses to form a homogeneous, cavityfree compound within a short period of time
	Durable
	Ozone-resistant
	No electrolytic corrosion
	Highly flexible
	Superior physical properties
Applications	Repairing of semi-conducting layer in medium voltage cables
	Electrical field smoothing
	For smoothing rough surfaces of connectors and cable lugs

Technical data

Materials	EPR-Base
Length L	9.1 m
Width B	19 mm
Thickness	0.76 mm
Colours	black
Temperature range min	-40 °C
Temperature range max	100 °C
Elongation at break	900 %
Tensile strength at break	3 MPa
Specific volume resistivity	10 Ω cm

Logistics data

Delivery scope	Conductive tape
Country of origin	Spain
Customs tariff number	40059100

EAN-UPC	4010311005546			
Base quantity	1	1	1	10
Base unit of measure	Piece	Piece	Piece	Piece
Alternate quantity	1	1	1	91
Alternative unit of measure	Piece	Bag1	Pack	Meter
Lenght	145	145	145	91000
Width	139	139	139	19
Height	57	57	57	0.76
Dimension unit	Millimetres	Millimetres	Millimetres	Millimetres
Volume	1.149	1.149	1.149	0.144
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	Cubic decimetres
Gross weight	0.193	0.193	0.193	1.93
Net weight	0.193	0.193	0.193	0.021
Weight unit	Kilogram	Kilogram	Kilogram	Kilogram