Technical-Data-Sheet

No. 64

Sealing tape

for permanently flexible sealing

Universally suitable, auto-amalgamating, to seal homogeneously or upholstering cables and conductors.



Product description

Article name	No. 64
Material number	125591
Characteristics	Self-amalgamating
	Corrosion-resistant
	Ozone-resistant
	Permanently flexible
	Excellent adherence to metal, glass rubber and plastic
	Superior physical properties
Applications	Sealing of cable and conductor interstices
	Repairing of damaged cable sheaths
	Water-resistant sealing of cable entry points
	Padding of cable insulation
	Suitable for connections using acrylic and epoxy resin compounds
	Protection against dust, moisture and corrosion

Technical-Data-Sheet

Technical data

Materials	Butyl-/Rubber based
Length L	1.5 m
Width B	38 mm
Thickness	3.2 mm
Colours	black
Tensile strength at break	0.1 MPa
Heat resistance min	-30 °C
Heat resistance max	80 °C
Specific volume resistivity	10^{12} Ω cm
Dielectric strength	23 kV/mm

Logistics data

Delivery scope	Sealing tape
Country of origin	France
Customs tariff number	40051000

EAN-UPC	4010311005584			
Base quantity	1	1	1	32
Base unit of measure	Piece	Piece	Piece	Piece
Alternate quantity	1	1520	1	1
Alternative unit of measure	Piece	Millimetre	Tin	Carton
Lenght	93	93	93	551
Width	90	90	90	250
Height	50	50	50	240
Dimension unit	Millimetres	Millimetres	Millimetres	Millimetres
Volume	0.419	0.419	0.419	33.06
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	Cubic decimetres
Gross weight	0.343	0.343	0.343	11.276
Net weight	0.343	0	0.343	10.976
Weight unit	Kilogram	Kilogram	Kilogram	Kilogram