Technical-Data-Sheet

DV-CU-V

Compression connector Cu

according to DIN 46267 without separator for low voltage

Strain-relieving connector (hexagonally compressed)
for copper conductors, suitable for joints.




Product description

Article name	DV-CU-V 35
Material number	125953
Applications	Connector for RM/SM (Class 2) copper conductors according to DIN EN 60228 (VDE 0295)
Family notes	To be used with suitable crimping tool with DIN inserts

Technical-Data-Sheet

Technical data



Test standards	DIN 46267-1
Materials	Copper tin-plated
Length L	50 mm
Diameter D1	8.2 mm
Nominal cross section min	35 mm²
Nominal cross section max	35 mm²
Press die code K	12 mm

Logistics data

Delivery scope	Compression connectors
Country of origin	Poland
Customs tariff number	85369010

EAN-UPC	4010311053059			
Base quantity	1	1	100	
Base unit of measure	Piece	Piece	Piece	
Alternate quantity	1	1	1	
Alternative unit of measure	Piece	Bag1	Carton	
Lenght	47	47	145	
Width	13	13	97	
Height	13	13	100	
Dimension unit	Millimetres	Millimetres	Millimetres	
Volume	0.008	0.008	1.407	
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	
Gross weight	0.029	0.029	3.2	
Net weight	0.029	0.029	2.9	
Weight unit	Kilogram	Kilogram	Kilogram	