Technical-Data-Sheet

DK-CU-V

Compression cable lug Cu

for low and medium voltage

Cable lug (hexagonally compressed) for copper conductors, suitable for indoor cable terminations.



Product description

Article name	DK-CU-V 120/16
Material number	126077
Applications	Cable lug recommended for copper conductors RM/SM (class 2) according to DIN EN 60228 (VDE 0295)
Family notes	To be used with suitable crimping tool with DIN inserts

Technical data

Test standards	DIN 46235
	IEC 61238
Materials	Copper tin-plated
Length L	70 mm
Width B	32 mm
Diameter D1	15.5 mm
Diameter D2	17 mm
Diameter D3	21 mm
Nominal cross section min	120 mm²
Press die code K	20 mm
Length A	35 mm

Logistics data

Delivery scope	Compression cable lug
Country of origin	Slovakia
Customs tariff number	85369010

EAN-UPC	4010311052540			
Base quantity	1	1	50	
Base unit of measure	Piece	Piece	Piece	
Alternate quantity	1	1	1	
Alternative unit of measure	Piece	Bag1	Carton	
Lenght	88	88	190	
Width	29	29	165	
Height	20	20	75	
Dimension unit	Millimetres	Millimetres	Millimetres	
Volume	0.051	0.051	2.351	
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	
Gross weight	0.108	0.108	5.7	
Net weight	0.108	0.108	5.4	
Weight unit	Kilogram	Kilogram	Kilogram	