V, VI, VS

Screw connector Al-Cu

for low voltage

Screw connector for aluminium and copper conductors with grub screws.



Product description

Article name	VI 50-150
Material number	126165
Applications	For connecting conductors RM/SM (class 2), RE/SE (class 1) according to DIN EN/IEC 60228 (VDE 0295)

Technical data

Materials	Aluminium
Selection Note	VI = Insulated
Nominal cross section SE min	50 mm²
Nominal cross section SE max	95 mm²
Nominal cross section RE min	50 mm²
Nominal cross section RE max	150 mm²

Logistics data

Delivery scope	Screw connector
Country of origin	Germany
Customs tariff number	85369010

EAN-UPC	4010311062082			
Base quantity	1	1	70	
Base unit of measure	Piece	Piece	Piece	
Alternate quantity	1	1	1	
Alternative unit of measure	Piece	Bag1	Carton	
Lenght	86	86	280	
Width	37	37	225	
Height	25	25	145	
Dimension unit	Millimetres	Millimetres	Millimetres	
Volume	0.08	0.08	9.135	
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	
Gross weight	0.142	0.142	10.24	
Net weight	0.142	0.142	9.94	
Weight unit	Kilogram	Kilogram	Kilogram	