V, VI, VS

Screw connector Al-Cu

for low voltage

Screw connector for aluminium and copper conductors with grub screws.



Product description

Article name	VS 4-50
Material number	126214
Applications	For connecting conductors RM/SM (class 2), RE/SE (class 1) according to DIN EN/IEC 60228 (VDE 0295)

Technical data

Materials	Aluminium
Selection Note	VS = For heat shrinkable cable joints
Nominal cross section RM min	4 mm²
Nominal cross section RM max	35 mm²
Nominal cross section SM min	4 mm²
Nominal cross section SM max	35 mm²
Nominal cross section SE min	4 mm²
Nominal cross section SE max	50 mm²
Nominal cross section RE min	4 mm²
Nominal cross section RE max	50 mm²

Logistics data

Delivery scope	Screw connector
Country of origin	Poland
Customs tariff number	85369010

EAN-UPC	4010311062419			
Base quantity	1	1	100	
Base unit of measure	Piece	Piece	Piece	
Alternate quantity	1	1	1	
Alternative unit of measure	Piece	Bag1	Carton	
Lenght	37	37	195	
Width	15	15	150	
Height	15	15	70	
Dimension unit	Millimetres	Millimetres	Millimetres	
Volume	0.008	0.008	2.048	
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	
Gross weight	0.016	0.016	1.9	
Net weight	0.016	0.016	1.6	
Weight unit	Kilogram	Kilogram	Kilogram	