Technical-Data-Sheet

LW..., LHS

Splice cassette system

for fibre optic cables



Product description

Article name	LZW-L Strain relief left
Material number	126497
Characteristics	Flange mount strain relief for fibre optic cables
	Insertion opening for up to max. 12 glass fibres
	Flame-retardant plastic housing
	All current splice holders are interlockable (with anti-rotation protection)
	Easy attachment of stranded conductors
	Counter support bracket for easy insertion of glass fibres
	The conductors can be easily redirected to other levels
	Halogen-free
	Mechanical strain relief
Applications	Compact joints

	Coupler housing for joints or trays
	Mechanical protection for spliced optical fibres
	Drawer application (modular compartments), choice of stress relief bushing for easy assembly of pigtail
	Vertical compartments for multifunctionality and flexibility
	Where high performance fibre optic cabling and connections are required
Family notes	Recommended operating temperature range of -55 to +70 °C

Technical data

Materials	Ethyl vinyl acetate insert
	Flexible heat shrinkable tube
	Stainless steel bar
Colours	blue

Logistics data

Delivery scope	25 Strain reliefs
Country of origin	Germany
Customs tariff number	39269097

EAN-UPC	4010311013831			
Base quantity	1	25	500	10000
Base unit of measure	Piece	Piece	Piece	Piece
Alternate quantity	1	1	1	1
Alternative unit of measure	Piece	Bag	Carton	Pal. OW
Lenght	87	245	600	1200
Width	60	160	370	800
Height	10	35	200	1200
Dimension unit	Millimetres	Millimetres	Millimetres	Millimetres
Volume	0.052	1.372	44.4	1152
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	Cubic decimetres
Gross weight	0.011	0.28	5.8	128.2
Net weight	0.011	0.275	5.5	110
Weight unit	Kilogram	Kilogram	Kilogram	Kilogram