LW..., LHS

Splice cassette system

for fibre optic cables



Product description

Article name	LWH-L Splice holder 6 x shrink
Material number	126499
Characteristics	Flange mount strain relief for fibre optic cables
	Insertion opening for up to max. 12 glass fibres
	Flame-retardant plastic housing
	All current splice holders are interlockable (with anti-rotation protection)
	Easy attachment of stranded conductors
	Counter support bracket for easy insertion of glass fibres
	The conductors can be easily redirected to other levels
	Halogen-free
	Mechanical strain relief
Applications	Compact joints
	Coupler housing for joints or trays
	Mechanical protection for spliced optical fibres
	Drawer application (modular compartments), choice of stress relief bushing for easy assembly of pigtail
	Vertical compartments for multifunctionality and flexibility
	Where high performance fibre optic cabling and connections are required
Family notes	Recommended operating temperature range of -55 to +70 °C

Technical data

Materials	Ethyl vinyl acetate insert
	Flexible heat shrinkable tube
	Stainless steel bar
Colours	transparent color

Logistics data

Delivery scope	50 Splice holder
Country of origin	Germany
Customs tariff number	39269097

EAN-UPC	4010311012506			
Base quantity	1	50	50	1500
Base unit of measure	Piece	Piece	Piece	Piece
Alternate quantity	1	1	1	1
Alternative unit of measure	Piece	Bag	Pack	Carton
Lenght	45	135	135	370
Width	30	110	110	240
Height	7	35	35	200
Dimension unit	Millimetres	Millimetres	Millimetres	Millimetres
Volume	0.009	0.52	0.52	17.76
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	Cubic decimetres
Gross weight	0.001	0.055	0.055	1.8
Net weight	0.001	0.05	0.05	1.5
Weight unit	Kilogram	Kilogram	Kilogram	Kilogram