Technical-Data-Sheet

No. 128

PVC insulation tape thin

for marking bundling and insulating

Flexible, UV-resistant PVC insulation tape.



Product description

Article name	No. 128 white
Material number	145801
Characteristics	Synthetic rubber adhesive
	Very good resistance to abrasion, corrosion and moisture
	Stabilized against UV rays
	High flexibility
	Withstands high electrical stresses
	Good adhesive properties
	Easy processing
	Oil-resistant
	Resistant to dilute acids and alkalis
Applications	Sealing
	Padding of cable insulation
	Bundling
	Reinforcing
	As insulation of electrical and telecommunication cables
	Colour-coding

Technical data

Test standards	IEC 60454-3-1-5
Materials	PVC
Length L	25 m
Width B	19 mm
Thickness	0.15 mm
Colours	white
Adhesive strength	1.8 N/cm
Adhesive strength (associated standard)	IEC 60454-2
Elongation at break	170 %
Elongation at break (associated standard)	IEC 60454-2
Tensile strength at break	30 N/cm
Tensile strength at break (associated standard)	IEC 60454-2
Unwinding force	1.8 N/cm
Unwinding force (associated standard)	IEC 60454-2
Operation temperature min	0 °C
Operation temperature max	90 °C
Operation temperature (associated standard)	IEC 60454-2
Dielectric strength	40 kV/mm
Dielectric strength (associated standard)	IEC 60454-2

Logistics data

Delivery scope	PVC insulation tape
Country of origin	Italy
Customs tariff number	39191012

EAN-UPC	4010311013664			
Base quantity	1	1	10	120
Base unit of measure	Piece	Piece	Piece	Piece
Alternate quantity	1	1	1	1
Alternative unit of measure	Piece	Roll	Bundle	Carton
Lenght	92	92	92	310
Width	92	92	92	260
Height	21.2	21.2	212	215
Dimension unit	Millimetres	Millimetres	Millimetres	Millimetres
Volume	0.179	0.179	1.794	17.329
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	Cubic decimetres
Gross weight	0.081	0.081	0.815	10.02
Net weight	0.081	0.081	0.81	9.72
Weight unit	Kilogram	Kilogram	Kilogram	Kilogram