Technical-Data-Sheet

SMH1…5

Heat shrinkable straight-through joint

for unarmoured polymeric cables


Universally suitable for connecting polymeric cables or conductors insulated with PVC, PE and XLPE (e.g. N(A)YY, NYM, TT). Suitable for compression connectors on aluminium or copper cables.



Product description

Article name	SMH3 1.5-16
Material number	151500
Characteristics	Compact dimensions
	Wide conductor and cross-section range
	Resistant to chemical agents
	Resistant to alkaline earth elements
	Stabilized against UV rays
	Free from paint-wetting inhibiting substances
	Halogen-free
	Transversely waterproof
	High electrical insulating values
	High mechanical strength
Applications	Indoor
	Outdoor
	Underground
	Water
	Installation ducts
	Ductwork
Optional accessory	Compression connectors (see Connecting technology)

Technical data



Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
Length L1	400 mm
Nominal cross section Polymeric cable unarmoured per conductor 3x min	1.5 mm²
Nominal cross section Polymeric cable unarmoured per conductor 3x max	16 mm²

Logistics data

Delivery scope	Outer sleeve
	Inner sleeves
	Cleaning tissue
	Emery cloth
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39173900

EAN-UPC	4010311057194			
Base quantity	1	1	10	360
Base unit of measure	Piece	Piece	Piece	Piece
Alternate quantity	1	1	1	1
Alternative unit of measure	Piece	Bag1	Case	Pal. OW
Lenght	40	40	430	1200
Width	70	70	264	800
Height	425	425	160	1130
Dimension unit	Millimetres	Millimetres	Millimetres	Millimetres
Volume	1.19	1.19	18.163	1084.8
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	Cubic decimetres
Gross weight	0.11	0.11	1.105	57.8
Net weight	0.11	0.11	1.1	39.6
Weight unit	Kilogram	Kilogram	Kilogram	Kilogram