CAE-F

1-core outdoor slip-on cable termination

for 1-core polymeric cables

Contrax cable terminations CAE-F are suitable for all 1-core polymeric-insulated cables (PVC, PE, XLPE, EPR) with different types of semi-conductive layers (graphitecoated, removable or strippable) and screen design (wire or tape). Suitable for compression cable lugs.




Product description

Article name	CAE-F 24kV 35-120
Material number	199194
Characteristics	Silicone slip-on components for quick, safe and easy assembly
	Wide cross-section range
	Ready for immediate operation
Applications	Outdoor
Family notes	Can be used also for cables Um = 7,2 kV, then the minimum diameter over conductor insulation has to be checked.
Optional accessory	EGA earthing kit for cables with tape screen (see Connecting technology)
	Compression cable lugs (see Connecting technology)

Technical-Data-Sheet

Technical data



Voltage levels	U0/U (Um) 12/20 (24) kV - 12,7/22 (24) kV
Test standards	CENELEC HD 629.1
Length L	325 mm
Diameter over core insulation after removal of the outer conductive layer min	17.3 mm
Number of sheds per phase	4 Pieces
Diameter shed	87 mm
Nominal cross section 24 kV min	35 mm²
Nominal cross section 24 kV max	120 mm²

Logistics data

Delivery scope	3 One-piece slip-on silicone cable terminations with integrated stress control element
	Silicone tubes
	Sealing tape
	Assembly material
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	85469090

EAN-UPC	4010311054827			
Base quantity	1	1	84	
Base unit of measure	Piece	Piece	Piece	
Alternate quantity	1	1	1	
Alternative unit of measure	Piece	Carton	Pal. OW	
Lenght	383	383	1200	
Width	192	192	800	
Height	132	132	1130	
Dimension unit	Millimetres	Millimetres	Millimetres	
Volume	9.707	9.707	1084.8	
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	
Gross weight	1.032	1.032	104.888	
Net weight	1.032	1.032	86.688	
Weight unit	Kilogram	Kilogram	Kilogram	