CWS 400A

Elbow separable connector

for polymeric cables for outer cone system terminals type B


Cellplux elbow separable connectors CWS are suitable for connecting all polymeric- insulated 1-core cables (VPE, (H)EPR), with different types of semiconductive layers (graphite-coated or strippable) and screen design (wire or tape screen), to switching equipment and transformers having an outer cone system type B, up to maximum network voltage of 36 kV in accordance with EN 50180 and EN 50181.



Product description

Article name	CWS 400A 36kV 35-95 EGA
Material number	250726
Characteristics	With capacitive measuring point for voltage checking
	Suitable for various cone voltage sensors
	Routine tests (AC test, PD measurement, X-ray control)
	Outer semi-conductive layer made of semi-conductive EPDM provides protection from exposed electrical parts
	Cable sheath insulation fault test may be performed while under voltage
	For both copper and aluminium conductors
	Quick, safe and easy assembly
	Suitable for a wide range of applications due to integrated screw cable lug
Applications	Indoor
	Outdoor
Family notes	Separable connectors for alternative cross-sections and for class 5 conductors on request
Optional accessory	EGA earthing kit for cables with tape screen (see Connecting technology)

Technical data



Voltage levels	U0/U (Um) 6/10 (12) kV - 19/33 (36) kV
	U0/U (Um) 12/20 (24) kV - 19/33 (36) kV
Test standards	CENELEC HD 629.1
Length L	215 mm
Width B	107 mm
Heigth H	250 mm
Diameter over core insulation after removal of the outer conductive layer min	22 mm
Nominal cross section 24 kV min	95 mm²
Nominal cross section 24 kV max	95 mm²
Nominal cross section 36 kV min	35 mm²
Nominal cross section 36 kV max	95 mm²

Logistics data

Delivery scope	Set of 3 separable connectors
	Silicone field control elemens
	Earthing set
	Screw cable lugs for main conductor
	Assembly material
	Assembly instructions
Shelf life description	Unlimited shelf life
Storage temperatur max	50 °C
Storage temperatur min	0 °C
Country of origin	Germany
Customs tariff number	85479000

EAN-UPC	4010311134116			
Base quantity	1	1	32	
Base unit of measure	Piece	Piece	Piece	
Alternate quantity	1	1	1	
Alternative unit of measure	Piece	Carton	Pal. OW	
Lenght	377	377	1200	
Width	291	291	800	
Height	237	237	1130	
Dimension unit	Millimetres	Millimetres	Millimetres	
Volume	26.001	26.001	1084.8	
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	
Gross weight	5.24	5.24	185.88	
Net weight	5.24	5.24	167.68	
Weight unit	Kilogram	Kilogram	Kilogram	