Technical-Data-Sheet

KSMZ

Cable ties

with metal latch



Product description

Article name	KSMZ 4.5/290
Material number	369820
Characteristics	For demanding applications
	Smooth, rounded edges for safe and easy handling and assembly
	Internal gearing and rounded-off end to facilitate take-up, insertion and tightening
	Resistant to alkaline earth elements
	Resistant to mould and oil
	Stabilized against UV rays
	Resistant to dilute acids and alkalis
	Halogen-free
	Flame retardant
	Silicone free
Applications	Bundling
	Affixing
Family notes	Under standard conditions 9,81 N correspond to 1 kg

Technical data

Test standards	EN 62275
Materials	Polyamide 6.6
Holding force min	350 N
Bundle diameter max	76 mm
Length L	290 mm
Width B	4.5 mm
Colours	natural color
Flammability rating	UL 94 V2
Mounting temperature min	-5 °C
Mounting temperature max	40 °C
Operation temperature min	-40 °C
Operation temperature max	85 °C

Logistics data

Delivery scope	100 Cable ties
Shelf life description	At 50 % relative humidity
	After opening the bag, must be used rapidly
Storage temperatur max	23 °C
Country of origin	Italy
Customs tariff number	39269097

EAN-UPC	4010311180632			
Base quantity	1	100	100	5000
Base unit of measure	Piece	Piece	Piece	Piece
Alternate quantity	1	1	1	1
Alternative unit of measure	Piece	Bag	Pack	Carton
Lenght	323	430	430	570
Width	7.8	95	95	190
Height	3.5	35	35	320
Dimension unit	Millimetres	Millimetres	Millimetres	Millimetres
Volume	0.009	1.43	1.43	34.656
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	Cubic decimetres
Gross weight	0.002	0.205	0.205	10.3
Net weight	0.002	0.2	0.2	10
Weight unit	Kilogram	Kilogram	Kilogram	Kilogram