Technical-Data-Sheet

EASYCELL Branch...V

Gel branch joint

with branch-off block

Universally applicable for branching all polymeric cables and conductors (e.g. N(A)YY, NYM, H05) cross section range from 6 mm² to 25 mm². Suitable for aluminium and copper conductors.




Product description

Article name	EASYCELL 7 V
Material number	371167
Characteristics	Connector area completely sealed by gel
	Re-accessible and ready for immediate operation
	Multi range one-piece branch-off block
	High-quality shockproof plastic shells, flame retardant and UV-resistant
	Quick, safe and easy assembly
Applications	Indoor (Laying in buildings and on cable racks)
	Outdoor
	Underground
	Water (according to test standard)
Family notes	Main cable must not be cut.
Copyright	EASYCELL is a registered trademark of BBC Cellpack GmbH

Technical-Data-Sheet

Technical data



Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
	EN 60695-2-11
Length L	260 mm
Width B	130 mm
Heigth H	65 mm
Nominal cross section Main cable Polymeric cable unarmoured per conductor 3x min	16 mm²
Nominal cross section Main cable Polymeric cable unarmoured per conductor 3x max	25 mm²
Nominal cross section Branch cable Polymeric cable unarmoured per conductor 3x min	2.5 mm²
Nominal cross section Branch cable Polymeric cable unarmoured per conductor 3x max	25 mm²
Nominal cross section Main cable Polymeric cable unarmoured per conductor 4x min	16 mm²
Nominal cross section Main cable Polymeric cable unarmoured per conductor 4x max	25 mm²
Nominal cross section Branch cable Polymeric cable unarmoured per conductor 4x min	2.5 mm²
Nominal cross section Branch cable Polymeric cable unarmoured per conductor 4x max	25 mm²
Nominal cross section Main cable Polymeric cable unarmoured per conductor 5x min	16 mm²
Nominal cross section Main cable Polymeric cable unarmoured per conductor 5x max	25 mm²
Nominal cross section Branch cable Polymeric cable unarmoured per conductor 5x min	2.5 mm²
Nominal cross section Branch cable Polymeric cable unarmoured per conductor 5x max	25 mm²
Housing type	7
Number of housing	1 Pieces
Connector type	Branch-off block

Logistics data

Delivery scope	Gel branch joint
	Branch-off block
	Cable ties
	Allen key
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Italy
Customs tariff number	85369010

EAN-UPC	4010311182018			
Base quantity	1	1	15	270
Base unit of measure	Piece	Piece	Piece	Piece
Alternate quantity	1	1	1	1
Alternative unit of measure	Piece	Case	Carton	Pal. OW
Lenght	277	277	410	1200
Width	137	137	380	800
Height	84	84	370	1300
Dimension unit	Millimetres	Millimetres	Millimetres	Millimetres
Volume	3.188	3.188	57.646	1248
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	Cubic decimetres
Gross weight	1.37	1.37	20.85	388.1
Net weight	1.37	1.37	20.55	369.9
Weight unit	Kilogram	Kilogram	Kilogram	Kilogram