Technical-Data-Sheet

CTKS 630A

T-shaped separable coupling connector

for polymeric cables for separable connector type CTS

Cellplux T-shaped separable coupling connectors CTKS are suitable for connecting all polymeric-insulated 1-core cables VPE, (H)EPR), with different types of semi-conductive layers (graphite-coated or strippable) and screen design (wire or tape screen) to the back of T-shaped separable connectors type CTS.



Product description

Article name	CTKS 630A 36kV 35-95/CA
Material number	445175
Characteristics	With capacitive measuring point for voltage checking
	Suitable for various cone voltage sensors
	Routine tests (AC test, PD measurement, X-ray control)
	Outer semi-conductive layer made of semi-conductive EPDM provides protection from exposed electrical parts
	Cable sheath insulation fault test may be performed while under voltage
	For both copper and aluminium conductors
	Quick, safe and easy assembly
	Suitable for a wide range of applications due to integrated screw cable lug
Applications	Indoor
	Outdoor
Family notes	Separable connectors for alternative cross-sections and for class 5 conductors on request
Optional accessory	EGA earthing kit for cables with tape screen (see Connecting technology)

Technical data

Voltage levels	U0/U (Um) 6/10 (12) kV - 19/33 (36) kV
	U0/U (Um) 12/20 (24) kV - 19/33 (36) kV
Test standards	CENELEC HD 629.1
Length L	310 mm
Width B	85 mm
Heigth H	271 mm
Diameter over core insulation after removal of the outer conductive layer min	22 mm
Diameter over core insulation after removal of the outer conductive layer max	33.5 mm
Nominal cross section 24 kV min	95 mm²
Nominal cross section 24 kV max	95 mm²
Nominal cross section 36 kV min	35 mm²
Nominal cross section 36 kV max	95 mm²

Logistics data

Delivery scope	Set of 3 separable coupling connectors with pre-installed earthing clamp and earthing wirewith M12 cable lug
	Cable adapter for sealing and stress control
	Screw cable lugs for main conductor
	Protection cap with fixing tie
	Assembly material
	Assembly instructions
Shelf life description	Unlimited shelf life
Storage temperatur max	50 °C
Storage temperatur min	0 °C
Country of origin	Germany
Customs tariff number	85479000

EAN-UPC	4010311198378			
Base quantity	1	1	32	
Base unit of measure	Piece	Piece	Piece	
Alternate quantity	1	1	1	
Alternative unit of measure	Piece	Carton	Pal. OW	
Lenght	374	374	1200	
Width	288	288	800	
Height	237	237	1130	
Dimension unit	Millimetres	Millimetres	Millimetres	
Volume	25.528	25.528	1084.8	
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	
Gross weight	5.7	5.7	200.6	
Net weight	5.7	5.7	182.4	
Weight unit	Kilogram	Kilogram	Kilogram	