RF

Pressure spring

for permanently elastic contact



Product description

Article name	RF 0
Material number	456338
Characteristics	Corrosion-resistant
	Fatigue-proof
	Guarantees consistent radial contact stress
Applications	For cast resin, heat shrinkable and slip-on cable accessories
	Enables solder-free electrical connection of metal cable components (screen, armouring, metal sheath) and earthing elements (copper grounding wire, cooper mesh joint etc.)
Family notes	Pressure springs are no currentcarrying parts.

Technical data

Materials	Special stainless steel
Selection Note	10 Pressure springs
Width B	16 mm
Diameter cable min	6 mm
Diameter cable max	10 mm
Outer diameter	5.7 mm

Logistics data

Delivery scope	10 Pressure springs
Country of origin	Great Britain
Customs tariff number	73209010

EAN-UPC	4010311199610			
Base quantity	1	10	10	
Base unit of measure	Piece	Piece	Piece	
Alternate quantity	1	1	1	
Alternative unit of measure	Piece	Bag	Pack	
Lenght	139	139	139	
Width	82	82	82	
Height	25	25	25	
Dimension unit	Millimetres	Millimetres	Millimetres	
Volume	0.285	0.285	0.285	
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	
Gross weight	0.001	0.013	0.013	
Net weight	0.001	0.01	0.01	
Weight unit	Kilogram	Kilogram	Kilogram	