RF

Pressure spring

for permanently elastic contact



Product description

Article name	RF 2
Material number	456341
Characteristics	Corrosion-resistant
	Fatigue-proof
	Guarantees consistent radial contact stress
Applications	For cast resin, heat shrinkable and slip-on cable accessories
	Enables solder-free electrical connection of metal cable components (screen, armouring, metal sheath) and earthing elements (copper grounding wire, cooper mesh joint etc.)
Family notes	Pressure springs are no currentcarrying parts.

Technical data

Materials	Special stainless steel
Selection Note	10 Pressure springs
Width B	16 mm
Diameter cable min	17 mm
Diameter cable max	28 mm
Outer diameter	17.5 mm

Logistics data

Delivery scope	10 Pressure springs
Country of origin	Great Britain
Customs tariff number	73209010

EAN-UPC	4010311199641			
Base quantity	1	10	10	
Base unit of measure	Piece	Piece	Piece	
Alternate quantity	1	1	1	
Alternative unit of measure	Piece	Bag	Pack	
Lenght	128	128	128	
Width	62	62	62	
Height	27	27	27	
Dimension unit	Millimetres	Millimetres	Millimetres	
Volume	0.214	0.214	0.214	
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	
Gross weight	0.007	0.073	0.073	
Net weight	0.007	0.07	0.07	
Weight unit	Kilogram	Kilogram	Kilogram	