RF

Pressure spring

for permanently elastic contact



Product description

Article name	RF 5
Material number	456344
Characteristics	Corrosion-resistant
	Fatigue-proof
	Guarantees consistent radial contact stress
Applications	For cast resin, heat shrinkable and slip-on cable accessories
	Enables solder-free electrical connection of metal cable components (screen, armouring, metal sheath) and earthing elements (copper grounding wire, cooper mesh joint etc.)
Family notes	Pressure springs are no currentcarrying parts.

Technical data

Materials	Special stainless steel
Selection Note	10 Pressure springs
Width B	20 mm
Diameter cable min	44 mm
Diameter cable max	70 mm
Outer diameter	37.8 mm

Logistics data

Delivery scope	10 Pressure springs
Country of origin	Great Britain
Customs tariff number	73209010

EAN-UPC	4010311199672			
Base quantity	1	10	10	
Base unit of measure	Piece	Piece	Piece	
Alternate quantity	1	1	1	
Alternative unit of measure	Piece	Bag	Pack	
Lenght	141	141	141	
Width	113	113	113	
Height	47	47	47	
Dimension unit	Millimetres	Millimetres	Millimetres	
Volume	0.749	0.749	0.749	
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	
Gross weight	0.051	0.513	0.513	
Net weight	0.051	0.51	0.51	
Weight unit	Kilogram	Kilogram	Kilogram	