Technical-Data-Sheet

CABLE GLISS

Lubricant spray

for feeding cables and conductors



Product description

Article name	CABLE GLISS Spray
Material number	458286
Characteristics	Does not damage rubber, plastics, textiles or varnished surfaces
	Does not damage construction materials
	Does not dry out
	Non-adherent
	Suitable for use as moisture buffer
	Water-resistant
Applications	Feeding of cables and wires through electrical installation conduits

Technical data

Content	0.6 l
Colours	transparent color
Viscosity (20 °C)	1000 cP
Density	0.63 g/cm³
Heat resistance min	-50 °C
Heat resistance max	200 °C
Dielectric strength	12 kV/mm

Logistics data

Delivery scope	Lubricant spray
Country of origin	Germany
Customs tariff number	34039900

EAN-UPC	4010311201689			
Base quantity	1	1	12	840
Base unit of measure	Piece	Piece	Piece	Piece
Alternate quantity	1	1	1	1
Alternative unit of measure	Piece	Tin	Carton	Pal. EU
Lenght	65	65	275	1200
Width	65	65	210	800
Height	284	284	295	1660
Dimension unit	Millimetres	Millimetres	Millimetres	Millimetres
Volume	1.2	1.2	17.036	1593.6
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	Cubic decimetres
Gross weight	0.49	0.49	6.08	440.6
Net weight	0.49	0.49	5.88	411.6
Weight unit	Kilogram	Kilogram	Kilogram	Kilogram