CAMERA HEAD Ø 3,9 mm flexible - 1 m

for RC2 Inspection camera
Item no.: **20488**

VIDEO
RC2
Click here Video



Click here Productinformation

DATA

ITEM NO.	**20488**
WEIGHT KG	0,053 kg
DIMENSION	H 20 mm x DM 205 mm
CAMERA HEAD	100.000 Pixel (320 x 240)
LIGHTNING	2 x LED (dimmable)
PROTECTION CLASS	IP 67
ANGLE VIEW	54 °
DIAMETER	3,9 mm
EAN-CODE	9120045474961

ADVANTAGES

- Pipe inspection from Ø 4 mm
- Protection class IP67
- Suitable for RC2 inspection camera
- Angle of view 54°

DESCRIPTION

Flexible camera head, Ø 3.9 mm (extra-slim), for the RC2 inspection camera. Ideal for adjusting the viewing angle to suit hard-to-reach areas. Length: 1 m. Features a resolution of 100,000 pixels (320 x 240), IP67 protection rating, a 54° field of view, 2 integrated LEDs with 6-step dimmable LED lighting, and integrated autofocus.

Optimal application: Ideal for short distances with a flexible gooseneck. For inspections of cavity walls, plant, machinery, engines, ventilation systems, control or inspection systems. Ideal for complex cavities, tight corners, shafts, ducts, small passages and many other applications in hard-to-reach areas. Pipe inspection from Ø 4 mm.

Scope of supply: 1 x Camera probe Ø 3,9 mm flexible - Length: 1 m

INFORMATION

Compatible with:
RC2 Inspection camera
50 m - Item no.: 10141



Click here Productinformation